

REDFIRE

*Optic Not Included



SYSTEM SPECIFICATIONS

Lock Range:	300 Yards	Operating Time:	500 rounds
Target Velocity:	11 MPH	Batteries:	(2) CR-123A
Calculated Target Lock Time:	100ms	Weather Resistant:	IP67 Splash, Water & Dust Resistant
Tracking Precision:	2 Minutes of Angle	Compatible With:	User Supplied Optic
RapidLok™ Trigger System:	Proprietary trigger system ensures on target shot release by automatic ratiometric edge detection fire control.	Ammunition:	TP 300 AAC BO 120 gr OTM TP 300 AAC BO 120 gr Tac-TX Any Quality 300 BO 110 gr
Receivers:	7075-T6 Forged Aluminum; A3 Slick-Sided Upper	Handguard:	Midwest Industries™ M-Lok Full Length, Includes (3) 5-Slot M-Lok Rails
Barrel:	16" 416A Stainless Steel	Weight:	7 lbs
OAL:	36.25"	Twist Rate:	1:7

SYSTEM TOTAL: \$2,995*

HOW IT WORKS

TrackingPoint REDFire Technology enhances the AR-15 rifle platform with LIDAR Fire Control. Targets are identified by their range signatures.

Shot Sequence:

- Hold on target and partial pull trigger.
- When on target LED illuminates.
- Pull trigger to fire
- If misaligned with target LED turns off and REDFire holds off shot
- Round is released when back on target

PACKAGE INCLUDES

(1) 10-Round Magazine BLK

***INTRODUCTORY PRICE**